

P/N AN3DDH5A

Description

Fastener Length: 41/64", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

 SKU / Model:
 AN3DDH5A

 Minimum Qty (MOQ):
 5

 NSN:
 5306-00-559-8134

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 013280, Alum Bolts









^{*} See page 2 for technical characteristics

P/N AN3DDH5A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Minimum And 0.453 Inches Maximum
Fastener Length:	0.641 Inches Minimum And 0.688 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.234 Inches Minimum And 0.266 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-200 Fed Spec Single Material Response Overall Or Qq-a-225 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Oxide Film Overall And Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN3DDH5A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.