

P/N AN3H21A

Description

Fastener Length: 2-1/8", Thread: 10-32, Thread Length: 3/8",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN3H21A

Minimum Qty (MOQ): 20

NSN: 5306-00-182-2010

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN3H21A Specifications

Thread Class:	3a
Thread Length:	0.406 Inches Minimum
Fastener Length:	2.156 Inches Nominal
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.750 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN3H21A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.