

Description

length: 2-9/32", grip: 1-7/8", thread: 10-32, cadmium plated steel, undrilled shank, drilled head, AN3 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN3H22A |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-00-182-2011 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN3H22A Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Length: | 0.406 Inches Minimum |
| Fastener Length: | 2.281 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.109 Inches Minimum And 0.141 Inches Maximum |
| Width Between Flats: | 0.365 Inches Minimum And 0.377 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.875 Inches Nominal |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Mil-b-6812 Mil Spec All Material Responses Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN3H22A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.