

**Description**

length: 2-9/32", grip: 1-7/8", thread: 10-32, cadmium plated steel, undrilled shank, drilled head, AN3 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN3H22A
Minimum Qty (MOQ):	10
NSN:	5306-00-182-2011
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN3H22A Specifications

<b>Thread Class:</b>	3a
<b>Thread Length:</b>	0.406 Inches Minimum
<b>Fastener Length:</b>	2.281 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.109 Inches Minimum And 0.141 Inches Maximum
<b>Width Between Flats:</b>	0.365 Inches Minimum And 0.377 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	1.875 Inches Nominal
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Mil-b-6812 Mil Spec All Material Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN3H22A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.