

P/N AN3H25A

Description

Fastener Length: 2-11/16", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN3H25A
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-282-5842
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN3H25A Specifications

Thread Direction: Right-hand Thread Length: 0.375 Inches Minimum And 0.453 Inches Maximum Fastener Length: 2.641 Inches Minimum And 2.688 Inches Maximum Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.190 Inches Rominal Thread Diameter: 0.190 Inches Width Between Flats: 0.390 Inches Minimum And 2.266 Inches Maximum Hole Quantity: 1 Hole Type: 0.71led Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds		
Tread Length: 0.375 Inches Minimum And 0.453 Inches Maximum Fastener Length: 2.641 Inches Minimum And 2.688 Inches Maximum Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Width Between Flats: 0.046 Inches Nominal Nominal Thread Diameter: 0.190 Inches Grip Length: 2.234 Inches Minimum And 2.266 Inches Maximum Hole Quantity: 1 Hole Type: 0 prilled Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4037 Overall Material Document And Classification: Surface Treatment Surface Treatment Opcument And Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Coverall Cove	Thread Class:	3a
Fastener Length: 2.641 Inches Minimum And 2.688 Inches Maximum Head Style: Hexagon Mach Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Width Between Flats: 0.046 Inches Minimum And 0.377 Inches Maximum Hole Diameter: 0.190 Inches Grip Length: 2.234 Inches Minimum And 2.266 Inches Maximum Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 2.6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4.140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Mils-s6050 Mil Spec 3rd Material Response Overall Or Mils-s6084 Mil Spec 4th Material Response Overall Or Mils-s6059 Mil Spec 3rd Material Response Overall Or Mils-s6088 Mil Spec 4th Material Response Overall Or Mils-s6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Stufface Treatment Document And Classification: Overall And Classification: Cadmium Overall And Chromate Overall Document And Classification: Overall And Chromate Overall Document And Classification: Cadmium Overall And Chromate Overall	Thread Direction:	Right-hand
Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Mole Diameter: 0.404 Inches Nominal Nominal Thread Diameter: 0.190 Inches Grip Length: 2.234 Inches Minimum And 2.266 Inches Maximum Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 25000 Pounds Per Square Inch Hardness Rating: 26.00 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Material Document And Classification: Stufface Treatment: Cadmium Overall And Chromate Overall Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Creatment Ocument And Classification:	Thread Length:	0.375 Inches Minimum And 0.453 Inches Maximum
Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.190 Inches Grip Length: 2.234 Inches Minimum And 2.266 Inches Maximum Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Mil-s-6059 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec	Fastener Length:	2.641 Inches Minimum And 2.688 Inches Maximum
Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.190 Inches Grip Length: 2.234 Inches Minimum And 2.266 Inches Maximum Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd	Head Style:	Hexagon
Hole Diameter: 0.046 Inches Nominal O.190 Inches 0.190 Inches 2.234 Inches Minimum And 2.266 Inches Maximum 4.266 Inches Maximum 5.234 Inches Minimum And 2.266 Inches Maximum 5.234 Inches Minimum And 2.266 Inches Maximum 5.234 Inches Minimum And 2.266 Inches Maximum 5.234 Inches Minimum 5.234 Inches Minimum 6.234 Inches Maximum 6.234 Inches Ma	Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Nominal Thread Diameter: 0.190 Inches Grip Length: 2.234 Inches Minimum And 2.266 Inches Maximum Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec Std Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec Std Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec Std Material Response Overall Or Mil-s-6758 Mil Spec Std Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec Std Material Response Overall Or Mil-s-6758 Mil Spec	Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Grip Length: 2.234 Inches Minimum And 2.266 Inches Maximum Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds Per Square Inch Hexagon Flats Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification: Qq-9-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification: Qq-9-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Hole Diameter:	0.046 Inches Nominal
Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Stight of the Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Document And Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.190 Inches
Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Ma	Grip Length:	2.234 Inches Minimum And 2.266 Inches Maximum
Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-67	Hole Quantity:	1
Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Minimum Tensile Strength: Hardness Rating: Hole Configuration Style: Material: Material: Material Document And Classification: Surface Treatment: Cadmium Overall And Classification: Material: Document And Classification: Material: Document And Classification: Material: Cadmium Overall And Chromate Overall Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification: Minimum Tensile Strength: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hexagon Flats Steel Comp 4037 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 M	Features Provided:	Finished Head
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Ocument And Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Thread Quantity Per Inch:	32
Hole Configuration Style: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material: Material Document And Classification: Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Hole Configuration Style:	Hexagon Flats
Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Material:	
Surface Treatment Document And Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn
Document And Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN3H25A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.