

P/N AN4-37

Military-Fasteners.com

Description

length: 3-29/32, grip: 3-7/16", thread: 1/4-28, cadmium plated steel - drilled shank

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | AN437 |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-151-1134 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N AN4-37 Specifications

| Thread Class: | За |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Minimum And 0.516 Inches Maximum |
| Fastener Length: | 3.891 Inches Minimum And 3.938 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.140 Inches Minimum And 0.172 Inches Maximum |
| Width Between Flats: | 0.428 Inches Minimum And 0.440 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 3.422 Inches Minimum And 3.453 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 3.734 Inches Minimum First Hole And 3.766 Inches Maximum First Hole |
| Material: | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unf |
| | |

How to Order

Order this airframe bolt, drilled from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/AN4-37</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.