

**Description**

length: 21/32", grip: 3/16", thread: 1/4-28, cadmium plated steel, drilled shank, AN4 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN45
Minimum Qty (MOQ):	20
NSN:	5306-00-144-3704
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN4-5 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.468 Inches Minimum
<b>Fastener Length:</b>	0.656 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.140 Inches Minimum And 0.172 Inches Maximum
<b>Width Between Flats:</b>	0.428 Inches Minimum And 0.440 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Minimum First Hole
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.188 Inches Nominal
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	125 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	0.500 Inches Nominal First Hole
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Mil-b-6812 Mil Spec All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.