

P/N AN42B10

Description

length: 1-1/32", grip: 5/8", thread: 10-32, drilled shank

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN42B10

Minimum Qty (MOQ):

NSN: 5306-00-638-2221

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN42B10 Specifications

Thread Direction: Right-hand Thread Length: 0.391 Inches Minimum And 0.437 Inches Maximum Eye Inside Diameter: 0.190 Inches Minimum And 0.192 Inches Maximum Shoulder Thickness: 0.062 Inches Nominal Shank Length: 1.016 Inches Minimum And 1.062 Inches Maximum Eye Stock Thickness: 0.089 Inches Minimum And 0.099 Inches Maximum Shoulder Diameter: 0.437 Inches Nominal Shank Unthreaded Hole Diameter: 0.600 Inches Minimum First Hole And 0.080 Inches Maximum First Hole Overall Length: 1.686 Inches Nominal Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 1.25000 Pounds Per Square Inch Hardness Rating: 6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Thread Length: 0.391 Inches Minimum And 0.437 Inches Maximum Eye Inside Diameter: 0.190 Inches Minimum And 0.192 Inches Maximum Shoulder Thickness: 0.062 Inches Nominal Shank Length: 1.016 Inches Minimum And 1.062 Inches Maximum Eye Stock Thickness: 0.089 Inches Minimum And 0.099 Inches Maximum Shoulder Diameter: 0.437 Inches Nominal Shank Unthreaded Hole Diameter: 0.060 Inches Minimum First Hole And 0.080 Inches Maximum First Hole Diameter: 0.190 Inches Minimum First Hole And 0.080 Inches Maximum First Hole Thread Quantity Per Inch: 32 Minimum Tensile Strength: 1.25000 Pounds Per Square Inch
Eye Inside Diameter: 0.190 Inches Minimum And 0.192 Inches Maximum Shoulder Thickness: 0.062 Inches Nominal Shank Length: 1.016 Inches Minimum And 1.062 Inches Maximum Eye Stock Thickness: 0.089 Inches Minimum And 0.099 Inches Maximum Shoulder Diameter: 0.437 Inches Nominal Shank Unthreaded Hole Diameter: 0.060 Inches Minimum First Hole And 0.080 Inches Maximum First Hole Overall Length: 1.686 Inches Nominal Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Shoulder Thickness: 0.062 Inches Nominal Shank Length: 1.016 Inches Minimum And 1.062 Inches Maximum Eye Stock Thickness: 0.089 Inches Minimum And 0.099 Inches Maximum Shoulder Diameter: 0.437 Inches Nominal Shank Unthreaded Hole Diameter: 0.060 Inches Minimum First Hole And 0.080 Inches Maximum First Hole Diameter: 0.1686 Inches Nominal Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Shank Length: Eye Stock Thickness: 0.089 Inches Minimum And 0.099 Inches Maximum Shoulder Diameter: 0.437 Inches Nominal Shank Unthreaded Hole Diameter: 0.060 Inches Minimum First Hole And 0.080 Inches Maximum First Hole Overall Length: 1.686 Inches Nominal Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Eye Stock Thickness: 0.089 Inches Minimum And 0.099 Inches Maximum Shoulder Diameter: 0.437 Inches Nominal Shank Unthreaded Hole Diameter: 0.060 Inches Minimum First Hole And 0.080 Inches Maximum First Hole Overall Length: 1.686 Inches Nominal Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Shoulder Diameter: 0.437 Inches Nominal Shank Unthreaded Hole Diameter: 0.060 Inches Minimum First Hole And 0.080 Inches Maximum First Hole Overall Length: 1.686 Inches Nominal Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Shank Unthreaded Hole Diameter: Overall Length: 1.686 Inches Nominal Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Diameter: Overall Length: Nominal Thread Diameter: O.060 Inches Minimum First Hole And 0.080 Inches Maximum First Hole 1.686 Inches Nominal Nominal Thread Diameter: O.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Minimum Tensile Strength: 125000 Pounds Per Square Inch
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Threaded End To Shank Hole Center: 0.875 Inches Minimum First Hole And 0.906 Inches Maximum First Hole
Eye Outside Width: 0.437 Inches Nominal
Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 As Std 6th Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unf

How to Order

Order this eye bolt from our inventory online by visiting https://military-fasteners.com/bolts/eye+bolts/AN42B10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.