

P/N AN42B14

Description

Thread: 10-32, Length: 2-1/4", Thread Length: 3/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

AN42B-14

SKU / Model: AN42B14

Minimum Qty (MOQ): 2

NSN: 5306-00-141-4553

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN42B14 Specifications

Thread Direction: Right-hand Thread Direction: Right-hand Thread Length: 0.406 Inches Minimum And 0.192 Inches Maximum Shoulder Thickness: 0.062 Inches Nominal Shank Length: 1.515 Inches Minimum And 1.562 Inches Maximum Shoulder Diameter: 0.438 Inches Nominal Shank Unthreaded Hole Diameter: 0.070 Inches Nominal First Hole Diameter: 0.070 Inches Nominal First Hole Diameter: 0.109 Inches Nominal First Hole Distance From Center Of Exp Distance From Center Of Exp Distance From Center Of Exp Distance From Threaded End To Shank Hole Center: 0.109 Inches Nominal First Hole Distance From Threaded End To Shank Hole Center: 0.109 Inches Nominal First Hole Distance From Threaded End To Shank Hole Center: 0.109 Inches Nominal First Hole Distance From Threaded End To Shank Hole Center: 0.109 Inches Nominal First Hole Distance From Threaded Plank D		
Thread Length: 0.406 Inches Minimum And 0.192 Inches Maximum Eye Inside Diameter: 0.962 Inches Minimum And 0.192 Inches Maximum Shoulder Thickness: 0.962 Inches Minimum And 1.562 Inches Maximum Eye Stock Thickness: 0.949 Inches Nominal Shoulder Diameter: 0.438 Inches Nominal Shank Unthreaded Hole Diameter: 0.907 Inches Nominal First Hole Overall Length: 2.188 Inches Nominal Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 3. Hardness Rating: 2.6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 2.6.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Hardness Rating: 2.9.2 Inches Nominal Distance From Center Of Eye To Shank End: 1.9.35 Inches Nominal To Shank Hole Center: 1.9.35 Inches Nominal Material: 3.48 Inches Nominal Material: 5.8ed Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8730 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil	Thread Class:	3a
Eye Inside Diameter: 0.190 Inches Minimum And 0.192 Inches Maximum Shoulder Thickness: 0.602 Inches Nominal Eye Stock Thickness: 0.094 Inches Nominal By Stock Thickness: 0.094 Inches Nominal Shank Luthreaded Hole Diameter: 0.707 Inches Nominal First Hole Overall Length: 2.188 Inches Nominal Nominal Thread Diameter: 1.910 Inches Nominal Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Spatial 3.931 Inches Nominal Distance From Threaded End 3.931 Inches Nominal Distance From Threaded End 3.931 Inches Nominal Bistance From Threaded End 3.931 Inches Nominal First Hole Distance From Threaded End 3.931 Inches Nominal First Hole Be Outside Width: 3.682 Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Miles-6050 Mil Spec 3rd Material Response Overall Or Miles-6050 Mil Spec 3rd Material Response Overall Or Miles-6050 Mil Spec 3rd Material Response Overall Or Miles-6050 Miles Peop	Thread Direction:	Right-hand
Shoulder Thickness: 0.062 Inches Nominal Shank Length: 1.515 Inches Minimum And 1.562 Inches Maximum Eye Stock Thickness: 0.094 Inches Nominal Shoulder Diameter: 0.438 Inches Nominal First Hole Owerall Length: 2.188 Inches Nominal First Hole Overall Length: 2.188 Inches Nominal Owerall Length: 1.90 Inches Mominal Thread Diameter: 2.5000 Pounds Per Square Inch Minimum Tensile Strength: 2.60 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 2.60 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Usbance From Center Ofts by Shank End: 3.93 Inches Nominal Distance From Threaded End: 3.93 Inches Nominal First Hole Stance From Threaded End: 3.93 Inches Nominal First Hole Stance From Threaded End: 3.93 Inches Nominal First Hole Stance From Threaded End: 3.93 Inches Nominal First Hole Stance From Threaded End: 3.94 Inches Nominal First Hole Stance From Threaded End: 3.94 Inches Nominal First Hole Stance From Threaded End: 3.95 Inches Nominal First Hole Stance From Threaded End: 3.95 Inches Nominal First Hole <th>Thread Length:</th> <th>0.406 Inches Minimum</th>	Thread Length:	0.406 Inches Minimum
Shank Length: 1.515 Inches Minimum And 1.562 Inches Maximum Eye Stock Thickness: 0.094 Inches Nominal Shank Unthreaded Hole Diameter: 0.070 Inches Nominal First Hole Shank Unthreaded Hole Diameter: 0.188 Inches Nominal First Hole Overall Length: 2.188 Inches Nominal Shominal Thread Diameter: 1.910 Inches Thread Quantity Per Inch. 25000 Pounds Per Square Inch Hardness Rating: 2.60 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 6.08 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 3.935 Inches Nominal Distance From Threaded End: 3.931 Inches Nominal First Hole Distance From Threaded End: 3.931 Inches Nominal First Hole Eye Outside Width: 0.438 Inches Nominal Material: Steel Comp 4.140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8730 Overall Or Steel Comp 9735 Overall Or Steel Comp 4130 Overall Material: Steel Comp 4.140 Overall Or Steel Comp 8740 Or Steel Comp 8730 Overall Or Mila-s-6050 Mil Spec 3rd Material Response Overall Or Mila-s-6050 Mil Spec	Eye Inside Diameter:	0.190 Inches Minimum And 0.192 Inches Maximum
Eye Stock Thickness: 0.094 Inches Nominal Shoulder Dlameter: 0.438 Inches Nominal Shank Unthreaded Hole Diameter: 0.070 Inches Nominal First Hole Diameter: 2.188 Inches Nominal Overall Length: 2.188 Inches Nominal Nominal Thread Djameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 15000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 1.935 Inches Nominal Distance From Threaded End To Shank Hole Center: 1.391 Inches Nominal First Hole Eye Outside Width: 0.438 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Materia	Shoulder Thickness:	0.062 Inches Nominal
Shoulder Diameter: 0.438 Inches Nominal Shank Unthreaded Hole Diameter: 0.70 Inches Nominal First Hole Overall Length: 2.188 Inches Nominal Overall Length: 0.190 Inches Nominal Thread Diameter: 1.90 Inches Thread Quantity Per Inch: 3 Hardness Rating: 1.5000 Pounds Per Square Inch Hardness Rating: 6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 6.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 1.935 Inches Nominal Distance From Threaded End To Shank End: 3.931 Inches Nominal First Hole Eye Outside Width: 0.438 Inches Nominal Maerial: 5teel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8830 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: 5teel Comp 4140 Overall Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall Material Document And Classification: 3keel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8740 Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil Spec 3rd Material Response Overall Or Mil-s-6059 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or M	Shank Length:	1.515 Inches Minimum And 1.562 Inches Maximum
Shank Unthreaded Hole Diameter: 0.070 Inches Nominal First Hole Overall Length: 2.188 Inches Nominal Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 3 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye of Shank End: 1,935 Inches Nominal Distance From Threaded End To Shank Hole Center: 3,931 Inches Nominal First Hole Stee Outside Width: 0.438 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall Material Document And Classification: Mili-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6075 Mil Spec 2nd Material Response Overall Or Mil-s-6095 Mil Spec 3rd Material Response Overall Or Mil-s-6095 Mil Spec 3rd Material Response Overall Or Mil-s-6095 Mil Spec 6th Material Response Overall Or Mil-s-6075 Mil Spec 5th Material Response Overall Or Mil-s-8095 Mil Spec 6th Material Response Overall Or Mil-s-6075 Mil Spec 5th Material Response Overall Or Mil-s-8095 Mil Spec 4th Material Respon	Eye Stock Thickness:	0.094 Inches Nominal
Diameter: Overall Length: Ournal Thread Diameter: Diamonial Thread Diamonial Diam	Shoulder Diameter:	0.438 Inches Nominal
Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye 1.935 Inches Nominal Distance From Threaded End To Shank Hole Center: 3.991 Inches Nominal First Hole Eye Outside Width: 0.438 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mill-s-5626 Mil Spec 1st Material Response Overall Or Mill-s-6049 Mil Spec 2nd Material Response Overall Or Mill-s-6050 Mil Spec 3rd Material Response Overall Or Mill-s-6050 Mil Spec 4th Material Response Overall Or Mill-s-6758 Mil Spec 5th Material Response Overall Or Mill-s-8695 Mil Spec 6th Material Response Overall Or Mill-s-6758 Mil Spec 5th Material Response Overall Or Mill-s-8695 Mil Spec 4th Material Response Overall Or Mill-s-6758 Mil Spec 5th Material Response Overall Or Mill-s-8695 Mil Spec 4th Material Response Overall Or Mill-s-6758 Mil Spec 5th Material Response Overall Or Mill-s-6050 Mill Spec 4th Material Response Overall Or Mill-s-6758 Mill Spec 4th Material Response Overall Or Mill-s-6050 Mill Spec 4th Material Response Overall Or Mill-s-6758 Mill Spec 5th Material Response Overall Or Mill-s-6050 Mill Spec 4th Material Response Overall O		0.070 Inches Nominal First Hole
Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye So Shank End: 1.935 Inches Nominal Distance From Threaded End To Shank Hole Center: 1.391 Inches Nominal First Hole Eye Outside Width: 0.438 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Miles-5626 Mil Spec 1st Material Response Overall Or Miles-6049 Mil Spec 2nd Material Response Overall Or Miles-6050 Mil Spec 3rd Material Response Overall Or Miles-6050 Mil Spec 3rd Material Response Overall Or Miles-6050 Mil Spec 3rd Material Response Overall Or Miles-6758 Mil Spec 5th Material Response Overall Or Miles-6695 Mil Spec 5th Material Response Overall Or Miles-6758 Mil Spec 5th Material Response Overall Or Miles-6758 Miles Spec 5th	Overall Length:	2.188 Inches Nominal
Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 1.935 Inches Nominal Distance From Threaded End So Shank Hole Center: 1.391 Inches Nominal First Hole Eye Outside Width: 0.438 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mill Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overal	Nominal Thread Diameter:	0.190 Inches
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 1.935 Inches Nominal Distance From Threaded End To Shank Hole Center: 1.391 Inches Nominal First Hole Eye Outside Width: 0.438 Inches Nominal Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall Material Document And Classification: Spec 6th Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-8098 Mil Spec 5th	Thread Quantity Per Inch:	32
Hardness Rating: 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 1.935 Inches Nominal Distance From Threaded End To Shank Hole Center: Eye Outside Width: 0.438 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4130 Overall Or Steel Comp 4140 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall Material Document And Classification: Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6798 Mil Spec 3nd Material Response Overall Or Mil-s-6798 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-6798 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-6798 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-6798 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-6798 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-6798 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-6798 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-6798 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-6798 Mil Spec 4th Material Response Overall Or Mi	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Distance From Center Of Eye To Shank End: Distance From Threaded End To Shank Hole Center: Eye Outside Width: O.438 Inches Nominal Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4037 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Steel Designator: Round, Closed W/shoulder	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
To Shank End: Distance From Threaded End To Shank Hole Center: Eye Outside Width: 0.438 Inches Nominal Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4037 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Surface Treatment Document And Chromate Overall And Chromate Overal	Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall
To Shank Hole Center: Eye Outside Width: 0.438 Inches Nominal Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 5th Mat	-	1.935 Inches Nominal
Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 5		1.391 Inches Nominal First Hole
Material: Material: Steel Comp 4037 Overall Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-	Eye Outside Width:	0.438 Inches Nominal
Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec	Material:	
Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6758 M	Material:	Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall
Surface Treatment Document And Classification: Style Designator: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Round, Closed W/shoulder		Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil
And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Style Designator: Round, Closed W/shoulder	Surface Treatment:	Cadmium Overall And Chromate Overall
		Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unf	Style Designator:	Round, Closed W/shoulder
	Thread Series Designator:	Unf

How to Order Order this eye bolt from our inventory online by visiting https://military-fasteners.com/bolts/eye+bolts/AN42B14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.