

## **P/N AN42B16A**

## **Description**

length: 1-25/32", grip: 1-3/8", thread: 10-32, undrilled shank

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN42B16A

Minimum Qty (MOQ): 5

NSN: 5306-00-271-6876

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N AN42B16A Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.391 Inches Minimum And 0.437 Inches Maximum
Eye Inside Diameter:	0.190 Inches Minimum And 0.192 Inches Maximum
Shoulder Thickness:	0.062 Inches Nominal
Shank Length:	1.766 Inches Minimum And 1.812 Inches Maximum
Eye Stock Thickness:	0.089 Inches Minimum And 0.099 Inches Maximum
Shoulder Diameter:	0.437 Inches Nominal
Overall Length:	2.437 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Eye Outside Width:	0.437 Inches Nominal
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Round, Closed W/shoulder
Thread Series Designator:	Unf

### **How to Order**

Order this eye bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/eye+bolts/AN42B16A">https://military-fasteners.com/bolts/eye+bolts/AN42B16A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="here">here</a> to complete your order.