

Description

length: 1-29/32", grip: 1-1/2", thread: 10-32, undrilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN42B17A
Minimum Qty (MOQ):	5
NSN:	5306-01-208-6701
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN42B17A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.374 Inches Minimum And 0.453 Inches Maximum
Eye Inside Diameter:	0.190 Inches Minimum And 0.192 Inches Maximum
Shoulder Thickness:	0.062 Inches Nominal
Shank Length:	1.890 Inches Minimum And 1.937 Inches Maximum
Eye Stock Thickness:	0.089 Inches Minimum And 0.099 Inches Maximum
Shoulder Diameter:	0.438 Inches Minimum
Overall Length:	1.890 Inches Minimum And 1.937 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall
Distance From Center Of Eye To Shank End:	2.312 Inches Nominal
Eye Outside Width:	0.438 Inches Nominal
Material:	Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Overall
Style Designator:	Round, Closed W/shoulder
Thread Series Designator:	Unf

How to Order

Order this eye bolt from our inventory online by visiting <https://military-fasteners.com/bolts/eye+bolts/AN42B17A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.