

P/N AN43B23A

Description

length: 2-13/32", grip: 1-15/16", thread: 1/4-28, undrilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN43B23A
Minimum Qty (MOQ): 1

NSN: 5306-00-421-9136

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN43B23A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.453 Inches Minimum And 0.500 Inches Maximum
Eye Inside Diameter:	0.190 Inches Minimum And 0.192 Inches Maximum
Shoulder Thickness:	0.062 Inches Minimum And 0.094 Inches Maximum
Shank Length:	2.390 Inches Minimum And 2.437 Inches Maximum
Eye Stock Diameter:	0.125 Inches Nominal
Eye Stock Thickness:	0.120 Inches Minimum And 0.130 Inches Maximum
Shoulder Diameter:	0.484 Inches Minimum And 0.516 Inches Maximum
Overall Length:	3.140 Inches Minimum And 3.170 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Center Of Eye To Shank End:	2.860 Inches Minimum And 2.891 Inches Maximum
Eye Outside Width:	0.484 Inches Minimum And 0.516 Inches Maximum
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Style Designator:	Round, Closed W/shoulder
Thread Series Designator:	Unf

How to Order

