

P/N AN44-14

Description

Thread: 1/4-24, Length: 2-3/8", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN4414

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-206-3892

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



P/N AN44-14 Specifications

Thread Direction: 3a Thread Direction: Night-hand Thread Length: 0.500 inches Minimum And 0.579 inches Maximum Eye Inside Diameter: 0.250 inches Minimum And 0.253 inches Maximum Shoulder Thickness: 0.094 inches Nominal Shank Length: 1.578 inches Minimum And 1.625 inches Maximum Eye Stock Thickness: 0.183 inches Minimum And 0.193 inches Maximum Shoulder Diameter: 0.625 inches Nominal Shank Unthreaded Hole Diameter: 0.625 inches Minimum First Hole And 0.086 inches Maximum First Hole Overall Length: 2.419 inches Nominal Nominal Thread Diameter: 2.419 inches Nominal Thread Quantity Per Inch: 24 Hardness Rating: 25000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Cher Of Eye To Shank Roll 2.111 Inches Minimum And 2.154 Inches Maximum First Hole But Center: 2.625 inches Nominal But Center: 2.625 inches Nominal Surface From Threaded End To Shank Roll Comp All All Overall Or Steel Comp B740 Overall Or Steel Comp B730 Overall Or Steel Comp B730 Overall Or Steel Comp B740 Overall Or Steel Comp B740 Overall Or Steel Comp B740 Overall Or Stee		
Thread Length: Distance From Center Of Eye To Shank End: Distance From Center Of Eye To Shank End: Distance From Center Of Eye To Shank End: Distance From Threaded End To Shank Hole Center: Eye Outside Width: Distance From Threaded End To Shank Hole End: Center	Thread Class:	3a
Eye Inside Diameter: 0.250 Inches Minimum And 0.253 Inches Maximum Shoulder Thickness: 0.094 Inches Nominal Shank Length: 1.578 Inches Minimum And 1.625 Inches Maximum Eye Stock Thickness: 0.83 Inches Minimum And 0.193 Inches Maximum Shoulder Diameter: 0.625 Inches Nominal Shank Unthreaded Hole Diameter: 0.066 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Overall Length: 2.419 Inches Nominal Nominal Thread Diameter: 0.312 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 1.25000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 2.111 Inches Minimum And 2.154 Inches Maximum Distance From Threaded End To Shank Polic Center: 2.405 Inches Minimum First Hole And 1.437 Inches Maximum First Hole Distance From Threaded End To Shank Polic Center: 3.405 Inches Minimum First Hole And 1.437 Inches Maximum First Hole Eye Outside Width: 0.625 Inches Nominal Surface Treatment: 3.405 Inches Minimum First Hole And 1.437 Inches Maximum First Hole Surface Treatment Document And Classification: 3.405 Inches Minimum Policial And Chroma	Thread Direction:	Right-hand
Shoulder Thickness: 0.094 Inches Nominal Shank Length: 1.578 Inches Minimum And 1.625 Inches Maximum Eye Stock Thickness: 0.183 Inches Minimum And 0.193 Inches Maximum Shoulder Diameter: 0.625 Inches Nominal Overall Length: 2.419 Inches Nominal Overall Length: 0.312 Inches Nominal Thread Diameter: 0.312 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 2.111 Inches Minimum And 2.154 Inches Maximum Distance From Threaded End To Shank Hole Center: 1.405 Inches Minimum First Hole And 1.437 Inches Maximum First Hole Eye Outside Width: 0.625 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Style Designator: Round, Closed W/shoulder	Thread Length:	0.500 Inches Minimum And 0.579 Inches Maximum
Shank Length:1.578 Inches Minimum And 1.625 Inches MaximumEye Stock Thickness:0.183 Inches Minimum And 0.193 Inches MaximumShoulder Diameter:0.625 Inches NominalShank Unthreaded Hole Diameter:0.066 Inches Minimum First Hole And 0.086 Inches Maximum First HoleOverall Length:2.419 Inches NominalNominal Thread Diameter:0.312 InchesThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Center Of Eye To Shank End:2.111 Inches Minimum And 2.154 Inches MaximumDistance From Threaded End To Shank Hole Center:1.405 Inches Minimum First Hole And 1.437 Inches Maximum First HoleEye Outside Width:0.625 Inches NominalMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallStyle Designator:Round, Closed W/shoulder	Eye Inside Diameter:	0.250 Inches Minimum And 0.253 Inches Maximum
Eye Stock Thickness: 0.183 Inches Minimum And 0.193 Inches Maximum Shoulder Diameter: 0.625 Inches Nominal Shank Unthreaded Hole Diameter: 0.066 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Overall Length: 2.419 Inches Nominal Nominal Thread Diameter: 0.312 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 2.111 Inches Minimum And 2.154 Inches Maximum Distance From Threaded End To Shank Hole Center: 1.405 Inches Minimum First Hole And 1.437 Inches Maximum First Hole Eye Outside Width: 0.625 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Style Designator: Round, Closed W/shoulder	Shoulder Thickness:	0.094 Inches Nominal
Shoulder Diameter:0.625 Inches NominalShank Unthreaded Hole Diameter:0.066 Inches Minimum First Hole And 0.086 Inches Maximum First HoleOverall Length:2.419 Inches NominalNominal Thread Diameter:0.312 InchesThread Quantity Per Inch:24Minimum Tensile Strength:1.25000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Center Of Eye To Shank End:2.111 Inches Minimum And 2.154 Inches MaximumDistance From Threaded End To Shank Hole Center:1.405 Inches Minimum First Hole And 1.437 Inches Maximum First HoleEye Outside Width:0.625 Inches NominalMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Oq-p-416.type 2.class 3 Fed Spec Single Treatment Response OverallStyle Designator:Round, Closed W/shoulder	Shank Length:	1.578 Inches Minimum And 1.625 Inches Maximum
Shank Unthreaded Hole Diameter:0.066 Inches Minimum First Hole And 0.086 Inches Maximum First HoleOverall Length:2.419 Inches NominalNominal Thread Diameter:0.312 InchesThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Center Of Eye To Shank End:2.111 Inches Minimum And 2.154 Inches MaximumDistance From Threaded End To Shank Hole Center:1.405 Inches Minimum First Hole And 1.437 Inches Maximum First HoleEye Outside Width:0.625 Inches NominalMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallStyle Designator:Round, Closed W/shoulder	Eye Stock Thickness:	0.183 Inches Minimum And 0.193 Inches Maximum
Overall Length: 2.419 Inches Nominal Nominal Thread Diameter: 0.312 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 2.111 Inches Minimum And 2.154 Inches Maximum Distance From Threaded End To Shank Hole Center: 1.405 Inches Minimum First Hole And 1.437 Inches Maximum First Hole Eye Outside Width: 0.625 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Style Designator: Round, Closed W/shoulder	Shoulder Diameter:	0.625 Inches Nominal
Nominal Thread Diameter: Thread Quantity Per Inch: Aliminum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 2.111 Inches Minimum And 2.154 Inches Maximum Distance From Threaded End To Shank Hole Center: Eye Outside Width: 0.625 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Style Designator: Round, Closed W/shoulder	Shank Unthreaded Hole Diameter:	0.066 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Thread Quantity Per Inch: Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 2.111 Inches Minimum And 2.154 Inches Maximum Distance From Threaded End To Shank Hole Center: Eye Outside Width: 0.625 Inches Nominal Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Style Designator: Round, Closed W/shoulder	Overall Length:	2.419 Inches Nominal
Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 2.111 Inches Minimum And 2.154 Inches Maximum Distance From Threaded End To Shank Hole Center: Eye Outside Width: 0.625 Inches Nominal Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Style Designator: Round, Closed W/shoulder	Nominal Thread Diameter:	0.312 Inches
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Center Of Eye To Shank End: 2.111 Inches Minimum And 2.154 Inches Maximum Distance From Threaded End To Shank Hole Center: 1.405 Inches Minimum First Hole And 1.437 Inches Maximum First Hole Eye Outside Width: 0.625 Inches Nominal Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Style Designator: Round, Closed W/shoulder	Thread Quantity Per Inch:	24
Distance From Center Of Eye To Shank End: Distance From Threaded End To Shank Hole Center: Eye Outside Width: O.625 Inches Nominal Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Style Designator: 2.111 Inches Minimum And 2.154 Inches Maximum First Hole And 1.437 Inches Maximum First Hole 1.405 Inches Minimum And 2.154 Inches Maximum First Hole And 1.437 Inches Maximum First Hole 1.405 Inches Minimum And 2.154 Inches Maximum First Hole And 1.437 Inches Maximum First Hole 1.405 Inches Minimum And 2.154 Inches Maximum First Hole And 1.437 Inches Maximum First Hole And 1.437 Inches Maximum First Hole 1.405 Inches Minimum And 2.154 Inches Maximum First Hole And 1.437 Inches Maximum First Hole 1.405 Inches Minimum And 2.154 Inches Maximum First Hole And 1.437 Inches Maximum First Hole 1.405 Inches Minimum And 2.154 Inches Maximum First Hole And 1.437 Inches Maximum First Hole 1.405 Inches Minimum And 2.154 Inches Maximum First Hole And 1.437 Inches Maximum First Hole And 1.437 Inches Maximum First Hole 1.405 Inches Maximum First Hole And 1.437 Inches Maximum First Hole And 1	Minimum Tensile Strength:	125000 Pounds Per Square Inch
End: Distance From Threaded End To Shank Hole Center: Eye Outside Width: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Style Designator: Round, Closed W/shoulder	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Center: Eye Outside Width: O.625 Inches Nominal Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Round, Closed W/shoulder	The state of the s	2.111 Inches Minimum And 2.154 Inches Maximum
Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Round, Closed W/shoulder		1.405 Inches Minimum First Hole And 1.437 Inches Maximum First Hole
Material: 4130 Overall Or Steel Comp 4037 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Round, Closed W/shoulder	Eye Outside Width:	0.625 Inches Nominal
Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Round, Closed W/shoulder	Material:	
Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Style Designator: Round, Closed W/shoulder	Surface Treatment:	Cadmium Overall And Chromate Overall
		Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
	Style Designator:	Round, Closed W/shoulder
Thread Series Designator: Unf	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/eye+bolts/AN44-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/eye+bolts/AN44-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/eye+bolts/AN44-14 and selecting the quantity you want then click "add to cart".