

P/N AN44-5

Military-Fasteners.com

#### Description

Thread: 1/4-24, Length: 1-19/32", Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	AN445
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-271-4821
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# **P/N AN44-5 Specifications**

Thread Class:3aThread Direction:Right-handThread Length:0.515 Inches Minimum And 0.562 Inches MaximumEye Inside Diameter:0.250 Inches Minimum And 0.253 Inches MaximumShoulder Thickness:0.094 Inches NominalShank Length:0.703 Inches Minimum And 0.750 Inches Maximum	
Thread Length:0.515 Inches Minimum And 0.562 Inches MaximumEye Inside Diameter:0.250 Inches Minimum And 0.253 Inches MaximumShoulder Thickness:0.094 Inches NominalShank Length:0.703 Inches Minimum And 0.750 Inches Maximum	
Eye Inside Diameter:0.250 Inches Minimum And 0.253 Inches MaximumShoulder Thickness:0.094 Inches NominalShank Length:0.703 Inches Minimum And 0.750 Inches Maximum	
Shoulder Thickness: 0.094 Inches Nominal   Shank Length: 0.703 Inches Minimum And 0.750 Inches Maximum	
Shank Length:   0.703 Inches Minimum And 0.750 Inches Maximum	
Eye Stock Thickness:   0.183 Inches Minimum And 0.193 Inches Maximum	
Shoulder Diameter: 0.625 Inches Nominal	
Shank Unthreaded Hole Diameter: 0.066 Inches Minimum First Hole And 0.086 Inches Maximum First Hole	
Overall Length: 1.609 Inches Nominal	
Nominal Thread Diameter: 0.312 Inches	
Thread Quantity Per Inch: 24	
Minimum Tensile Strength: 125000 Pounds Per Square Inch	
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall	
Distance From Threaded End To Shank Hole Center: 0.531 Inches Minimum First Hole And 0.562 Inches Maximum First Hole	
Eye Outside Width: 0.625 Inches Nominal	
Material:     Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall       Material:     4130 Overall Or Steel Comp 4037 Overall	omp
Surface Treatment: Cadmium Overall And Chromate Overall	
Surface Treatment Document And   Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall     Classification:   Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	
Style Designator: Round, Closed W/shoulder	
Thread Series Designator: Unf	

# How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/eye+bolts/AN44-5</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.