

**Description**

Bolt part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN44C4
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-230-3358
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN44-C4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.500 Inches Minimum And 0.579 Inches Maximum
<b>Eye Inside Diameter:</b>	0.250 Inches Minimum And 0.253 Inches Maximum
<b>Shoulder Thickness:</b>	0.078 Inches Minimum And 0.110 Inches Maximum
<b>Shank Length:</b>	0.578 Inches Minimum And 0.625 Inches Maximum
<b>Eye Stock Thickness:</b>	0.183 Inches Minimum And 0.193 Inches Maximum
<b>Shoulder Diameter:</b>	0.609 Inches Minimum And 0.641 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.066 Inches Minimum And 0.086 Inches Maximum First Hole
<b>Overall Length:</b>	1.484 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall
<b>Distance From Center Of Eye To Shank End:</b>	1.125 Inches Nominal
<b>Distance From Threaded End To Shank Hole Center:</b>	0.405 Inches Minimum And 0.437 Inches Maximum First Hole
<b>Eye Outside Width:</b>	0.609 Inches Minimum And 0.641 Inches Maximum
<b>Material:</b>	Steel Comp 431 Overall
<b>Material Document And Classification:</b>	Mil-s-18732 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Style Designator:</b>	Round, Closed W/shoulder
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/eye+bolts/AN44-C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.