

Description

Bolt part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN44C4
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-230-3358
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN44-C4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Minimum And 0.579 Inches Maximum
Eye Inside Diameter:	0.250 Inches Minimum And 0.253 Inches Maximum
Shoulder Thickness:	0.078 Inches Minimum And 0.110 Inches Maximum
Shank Length:	0.578 Inches Minimum And 0.625 Inches Maximum
Eye Stock Thickness:	0.183 Inches Minimum And 0.193 Inches Maximum
Shoulder Diameter:	0.609 Inches Minimum And 0.641 Inches Maximum
Shank Unthreaded Hole Diameter:	0.066 Inches Minimum And 0.086 Inches Maximum First Hole
Overall Length:	1.484 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall
Distance From Center Of Eye To Shank End:	1.125 Inches Nominal
Distance From Threaded End To Shank Hole Center:	0.405 Inches Minimum And 0.437 Inches Maximum First Hole
Eye Outside Width:	0.609 Inches Minimum And 0.641 Inches Maximum
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Style Designator:	Round, Closed W/shoulder
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/eye+bolts/AN44-C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.