

## **P/N AN44C6A**

### **Description**

Thread: 1/4-24, Length: 1-3/4", Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN44C6A

Minimum Qty (MOQ): 5 EA

NSN: 5306-01-086-8499

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



# **P/N AN44C6A Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Minimum And 0.579 Inches Maximum
Eye Inside Diameter:	0.250 Inches Minimum And 0.253 Inches Maximum
Shoulder Thickness:	0.094 Inches Nominal
Shank Length:	0.828 Inches Minimum And 0.875 Inches Maximum
Eye Stock Thickness:	0.183 Inches Minimum And 0.193 Inches Maximum
Shoulder Diameter:	0.625 Inches Nominal
Overall Length:	1.718 Inches Minimum And 1.765 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Center Of Eye To Shank End:	1.359 Inches Minimum And 1.406 Inches Maximum
Eye Outside Width:	0.625 Inches Nominal
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Style Designator:	Round, Closed W/shoulder
Thread Series Designator:	Unf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/eye+bolts/AN44C6A">https://military-fasteners.com/bolts/eye+bolts/AN44C6A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.