

Description

Thread: 3/8-24, Length: 2-7/32", Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN4611A
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-271-4792
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN46-11A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.624 Inches Minimum And 0.671 Inches Maximum
Eye Inside Diameter:	0.375 Inches Minimum And 0.378 Inches Maximum
Shoulder Thickness:	0.094 Inches Nominal
Shank Length:	1.188 Inches Minimum And 1.234 Inches Maximum
Eye Stock Thickness:	0.183 Inches Minimum And 0.193 Inches Maximum
Shoulder Diameter:	0.750 Inches Nominal
Shank Unthreaded Hole Diameter:	0.096 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Overall Length:	2.219 Inches Nominal
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 33.0 Rockwell C Maximum Overall
Distance From Threaded End To Shank Hole Center:	0.984 Inches Minimum First Hole And 1.016 Inches Maximum First Hole
Eye Outside Width:	0.750 Inches Nominal
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Round, Closed W/shoulder
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/eye+bolts/AN46-11A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.