

Description

Length: 1-13/32", grip: 15/16", thread: 1/4-28, corrosion resistant steel, undrilled shank, AN4 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN4C13A
Minimum Qty (MOQ):	10
NSN:	5306-00-156-2343
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN4C13A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.468 Inches Minimum
Fastener Length:	1.406 Inches Nominal
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.938 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Qq-s-770 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4C13A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.