

Description

length: 2-1/32", grip: 1-9/16", thread: 1/4-28 - corrosion resistant steel - drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN4C20 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-156-2277 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN4C20 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Minimum And 0.516 Inches Maximum |
| Fastener Length: | 2.016 Inches Minimum And 2.062 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.140 Inches Minimum And 0.172 Inches Maximum |
| Width Between Flats: | 0.428 Inches Minimum And 0.440 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.547 Inches Minimum And 1.578 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.859 Inches Minimum First Hole And 1.891 Inches Maximum First Hole |
| Material: | Steel Comp 431 Overall |
| Material Document And Classification: | Mil-s-18732 Mil Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4C20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.