

**Description**

Fastener Length: 3-1/4", Thread: 1/4-28, Thread Length: 15/32

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN4C32A                                   |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5306-00-639-2460                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN4C32A Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.469 Inches Minimum  |
| <b>Fastener Length:</b>                      | 3.281 Inches Nominal  |
| <b>Head Style:</b>                           | Hexagon   |
| <b>Head Height:</b>                          | 0.140 Inches Minimum And 0.172 Inches Maximum                       |
| <b>Width Between Flats:</b>                  | 0.428 Inches Minimum And 0.440 Inches Maximum                       |
| <b>Nominal Thread Diameter:</b>              | 0.250 Inches  |
| <b>Grip Length:</b>                          | 2.812 Inches Nominal  |
| <b>Features Provided:</b>                    | Finished Head   |
| <b>Thread Quantity Per Inch:</b>             | 28  |
| <b>Minimum Tensile Strength:</b>             | 125000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                      | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| <b>Material:</b>                             | Steel Corrosion Resisting Overall                                   |
| <b>Material Document And Classification:</b> | Qq-s-770 Fed Spec Single Material Response Overall                  |
| <b>Surface Treatment:</b>                    | Passivate Overall   |
| <b>Thread Series Designator:</b>             | Unf   |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4C32A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.