

# P/N AN4CH4A

## **Description**

length: 17/32", grip: 1/16", thread: 1/4-28, corrosion resistant steel, undrilled shank, drilled head

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN4CH4A

Minimum Qty (MOQ): 10

NSN: 5306-00-180-2778

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN4CH4A Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Minimum
Fastener Length:	0.531 Inches Nominal
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.062 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Qq-s-770 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/AN4CH4A">https://military-fasteners.com/bolts/machine+bolts/AN4CH4A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.