

## P/N AN4CH5A

## **Description**

length: 21/32", grip: 3/16", thread: 1/4-28, corrosion resistant steel, undrilled shank, drilled head

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN4CH5A

Minimum Qty (MOQ): 25

NSN: 5306-00-180-2779

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN4CH5A Specifications**

| Thread Class:                         | 3a   |
|---------------------------------------|--|
| Thread Direction:                     | Right-hand   |
| Thread Length:                        | 0.468 Inches Minimum                               |
| Fastener Length:                      | 0.656 Inches Nominal                               |
| Head Style:                           | Hexagon  |
| Head Height:                          | 0.140 Inches Minimum And 0.172 Inches Maximum      |
| Width Between Flats:                  | 0.428 Inches Minimum And 0.440 Inches Maximum      |
| Hole Diameter:                        | 0.046 Inches Nominal                               |
| Nominal Thread Diameter:              | 0.250 Inches                                       |
| Grip Length:                          | 0.188 Inches Nominal                               |
| Hole Quantity:                        | 1  |
| Hole Type:                            | Drilled  |
| Features Provided:                    | Finished Head                                      |
| Thread Quantity Per Inch:             | 28   |
| Minimum Tensile Strength:             | 125000 Pounds Per Square Inch                      |
| Hole Configuration Style:             | Hexagon Flats                                      |
| Material:                             | Steel Corrosion Resisting Overall                  |
| Material Document And Classification: | Qq-s-770 Fed Spec Single Material Response Overall |
| Surface Treatment:                    | Passivate Overall                                  |
| Thread Series Designator:             | Unf  |

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/AN4CH5A">https://military-fasteners.com/bolts/machine+bolts/AN4CH5A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.