

Description

length: 29/32", grip: 7/16", thread: 1/4-28 - corrosion resistant steel - undrilled shank - drilled head"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN4CH7A
Minimum Qty (MOQ):	10
NSN:	5306-00-182-1860
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN4CH7A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.515 Inches Maximum
Fastener Length:	0.891 Inches Minimum And 0.938 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.422 Inches Minimum And 0.453 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4CH7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.