



Military-Fasteners.com

P/N AN4CH7A

Description

length: 29/32", grip: 7/16", thread: 1/4-28 - corrosion resistant steel - undrilled shank - drilled head"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN4CH7A |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-00-182-1860 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN4CH7A Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Minimum And 0.515 Inches Maximum |
| Fastener Length: | 0.891 Inches Minimum And 0.938 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.140 Inches Minimum And 0.172 Inches Maximum |
| Width Between Flats: | 0.428 Inches Minimum And 0.440 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.422 Inches Minimum And 0.453 Inches Maximum |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Flats |
| Material: | Steel Comp 431 Overall |
| Material Document And Classification: | Mil-s-18732 Mil Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4CH7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.