

Description

Fastener Length: 2-9/64", Thread: 1/4-28, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN4DD21A
Minimum Qty (MOQ):	10
NSN:	5306-00-151-1444
ECCN:	EAR99
National Motor Freight:	013280, Alum Bolts

NO IMAGE
AVAILABLE

P/N AN4DD21A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	2.141 Inches Minimum And 2.188 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.672 Inches Minimum And 1.703 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-200 Fed Spec Single Material Response Overall Or Qq-a-225 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Oxide Film Overall And Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4DD21A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.