

Description

Fastener Length: 17/32", Thread: 1/4-28, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------|
| SKU / Model: | AN4DD4A |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-151-1076 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 013280, Alum Bolts |

NO IMAGE
AVAILABLE

P/N AN4DD4A Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.469 Inches Minimum |
| Fastener Length: | 0.531 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.140 Inches Minimum And 0.172 Inches Maximum |
| Width Between Flats: | 0.428 Inches Minimum And 0.440 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.062 Inches Nominal |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Material: | Aluminum Alloy 2024 Overall Or Aluminum Alloy Overall |
| Material Document And Classification: | Qq-a-267 Fed Spec 1st Material Response Overall Or Qq-a-268 Fed Spec 1st Material Response Overall Or Mil-w-7986 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Oxide Film Overall And Anodize Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4DD4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.