

Description

Fastener Length: 21/32", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN4DDH5A
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-208-9029
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013280, Alum Bolts

NO IMAGE
AVAILABLE

P/N AN4DDH5A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.468 Inches Minimum
Fastener Length:	0.656 Inches Nominal
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.188 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Aluminum Alloy 2024 Overall Or Aluminum Alloy Overall
Material Document And Classification:	Qq-a-267 Fed Spec 1st Material Response Overall Or Qq-a-268 Fed Spec 1st Material Response Overall Or Mil-w-7986 Mil Spec 2nd Material Response Overall
Surface Treatment:	Oxide Film Overall And Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4DDH5A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.