

**Description**

Fastener Length: 25/32", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 15/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN4DDH6A
Minimum Qty (MOQ):	1
NSN:	5306-00-275-9644
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013280, Alum Bolts

NO IMAGE  
AVAILABLE

## P/N AN4DDH6A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.469 Inches Minimum
<b>Fastener Length:</b>	0.781 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.140 Inches Minimum And 0.172 Inches Maximum
<b>Width Between Flats:</b>	0.428 Inches Minimum And 0.440 Inches Maximum
<b>Hole Diameter:</b>	0.046 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.312 Inches Nominal
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Hexagon Flats
<b>Material:</b>	Aluminum Alloy 2024 Overall Or Aluminum Alloy Overall
<b>Material Document And Classification:</b>	Qq-a-267 Fed Spec 1st Material Response Overall Or Qq-a-268 Fed Spec 1st Material Response Overall Or Mil-w-7986 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Oxide Film Overall And Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4DDH6A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.