

P/N AN4H10A

Description

length: 1-1/32", grip: 9/16", thread: 1/4-28, cadmium plated steel undrilled shank, drilled head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN4H10A

Minimum Qty (MOQ): 25

NSN: 5306-00-182-1958

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN4H10A Specifications

Thread Direction: Right-hand Thread Length: 0.469 Inches Minimum Fastener Length: 1.031 Inches Nominal Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.466 Inches Nominal Nominal Thread Diameter: 0.250 Inches Grip Length: 0.562 Inches Nominal Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds Per Square Inch Hardness Ra		
Thread Length: 0.469 Inches Minimum Fastener Length: 1.031 Inches Nominal Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Width Between Flats: 0.462 Inches Nominal Hole Diameter: 0.450 Inches Nominal Nominal Thread Diameter: 0.250 Inches Grip Length: 0.562 Inches Nominal Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 2 Hardness Rating: 0.560 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Onfiguration Style: Hexagon Flats Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Response Overall Or Ams 6300 Assa Std 4th Material Response Overall Or Mil-s-6059 Mil Spec 3rd Material Response Overall Or Ams 6300 Assa Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Surface Treatment Document And Classification: Page 10 Ams 6300 Assa Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Document And Classification: Page 10 Ams 6300 Assa Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Document And Classification: Page 10 Ams 6300 Assa Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Document And Classification: Page 10 Ams 6300 Assa Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Document And Classification: Page 10 Ams 6300 Assa Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Document And Classification: Page 10 Ams 6300 Assa Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Document And Classification: Page 10 Ams 6300 Assa Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or	Thread Class:	3a
Fastener Length: 1.031 Inches Nominal Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.046 Inches Nominal Hole Diameter: 0.562 Inches Nominal Nominal Thread Diameter: 0.562 Inches Nominal Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 2.6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Mili-s-6050 Mil Spec 2nd Material Response Overall Or Mili-s-6098 Mil Spec 3rd Material Response Overall Or Mili-s-6050 Mil Spec 2nd Material Response Overall Or Mili-s-6098 Mil Spec 3rd Material Response Overall Or Mili-s-6050 Mili Spec 2nd Material Response Overall Or Mili-s-6098 Mil Spec 3rd Material Response Overall Or Mili-s-6050 Mili Spec 2nd Material Response Overall Or Mili-s-6098 Mil Spec 3rd Material Response Overall Or Mili-s-6050 Mili Spec 2nd Material Response Overall Or Mili-s-6098 Mili Spec 3rd Material Response Overall Or Mili-s-6050 Mili Spec 2nd Material Response Overall Or Mili-s-6098 Mili Spec 3rd Material Response Overall Or Mili-s-6050 Mili Spec 2nd Material Response Overall Or Mili-s-6098 Mili Spec 3rd Material Response Overall Or Mili-s-6050 M	Thread Direction:	Right-hand
Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.250 Inches Onde Inches Nominal Nominal Thread Diameter: 0.552 Inches Nominal Hole Quantity: 1 Hole Quantity: 1 Hole Type: Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 25000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4140 Overall Or Steel Comp 4150 Overall Or Steel Comp 4150 Overall Or Steel Comp 4150 Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6026 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6026 Mil Spec 6th Material Response Overall Or Mil-s-6026 Mil Spec 6th Material Response Overall Or Mil-s-6026 Mil Spec Teatment: Ocument And Classification: Park Steel Comp 416, type 2, class 3 Fed Spec All Treatment Response Overall Classification: Park Steel Comp 416, type 2, class 3 Fed Spec All Treatment Response Overall	Thread Length:	0.469 Inches Minimum
Head Height: 0.40 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.550 Inches Grip Length: 0.550 Inches Grip Length: 0.550 Inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 25000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Heagon Flats Waterial: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Classification: Supec 6th Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Supec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Surface Treatment: Cadmium Overall And Chromate Overall Ocument And Classification: Q-p-416.type 2,class 3 Fed Spec All Treatment Responses Overall Ocument And Classification: Overall And Chromate Overall Or Mil-s-6050 Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall	Fastener Length:	1.031 Inches Nominal
Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.250 Inches Grip Length: 0.562 Inches Nominal Hole Quantity: 1 Hole Quantity: 1 Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Material Document And Classification: Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Ocument And Classification:	Head Style:	Hexagon
Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.250 Inches Grip Length: 0.562 Inches Nominal Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6026 Mil Spec 5th Material Response Overall Or Mil-s-6056 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 5th Material Response Overall Or Mil-s-6056 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Sp	Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Nominal Thread Diameter: 0.250 Inches Grip Length: 0.562 Inches Nominal Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Heagon Flats Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mali-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec Treatment: Cadmium Overall And Chromate Overall Ocument And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Ocument And Classification:	Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Grip Length: 0.562 Inches Nominal Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or	Hole Diameter:	0.046 Inches Nominal
Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Material Document And Classification: Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6060 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6050 M	Nominal Thread Diameter:	0.250 Inches
Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th	Grip Length:	0.562 Inches Nominal
Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 46.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Material: Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec Treatment Cadmium Overall And Chromate Overall Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Hole Quantity:	1
Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Material Document And Classification: Wil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Minimum Tensile Strength: Hardness Rating: Hole Configuration Style: Material: Material Document And Classification: Surface Treatment: Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall C Maximum Overall C Maximum Overall C Maximum Overall C Maximum Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 4140 Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil	Features Provided:	Finished Head
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Thread Quantity Per Inch:	28
Hole Configuration Style: Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 4140 Overall Or Steel Comp 4140 Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Ove	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 4140 Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material: Material Document And Classification: Steel Comp 4140 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758	Hole Configuration Style:	Hexagon Flats
Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil	Material:	
Surface Treatment Document And Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Material Document And Classification:	Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil
Document And Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN4H10A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.