

P/N AN4H12A

Description

length: 1-9/32", grip: 13/16", thread: 1/4-28, cadmium plated steel undrilled shank, drilled head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN4H12A

Minimum Qty (MOQ): 25

NSN: 5306-00-182-1960


ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN4H12A Specifications

Thread Direction: Right-hand Thread Length: 0.438 Inches Minimum And 0.515 Inches Maximum Fastener Length: 1.266 Inches Minimum And 1.312 Inches Maximum Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.250 Inches Grip Length: 0.797 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Type: 0.791 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds Per Square Inch Hole Configuration Style: Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4037 Overall Material Document And Classification: Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5t		
Thread Length: 0.438 Inches Minimum And 0.515 Inches Maximum Fastener Length: 1.266 Inches Minimum And 1.312 Inches Maximum Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Width Between Flats: 0.450 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.797 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Type: 0.799 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Type: 0.718 Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4037 Overall Material: Steel Comp 4037 Overall Material Document And Classification: 404 Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6030 Mis Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spe	Thread Class:	3a
Fastener Length: 1.266 Inches Minimum And 1.312 Inches Maximum Head Style: Hexagon Width Between Flats: 0.428 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.250 Inches Grip Length: 0.797 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 2 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 2.6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4037 Overall Material: Steel Comp 4037 Overall Or Steel Comp 8730 Overall Or Mili-s-6039 Mil Spec 2nd Material Response Overall Or Mili-s-6050 Mil Spec 3rd Material Response Overall Or Mili-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Stuface Treatment Document And Classification: Variable And Overall And Chromate Overall Document And Classification: Variable And Overall And Chromate Overall Document And Classification: Variable And Overall And Chromate Overall Or Mili-s-6059 Overall Or Mili-s-6059 Mil Spec 3 Fed Spec All Treatment Responses Overall Document And Classification: Variable	Thread Direction:	Right-hand
Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Mobinal Thread Diameter: 0.250 Inches Grip Length: 0.797 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 25.000 Pounds Per Square Inch Hardness Rating: 26.000 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Document And Classification: Qq-p-416.type 2.class 3 Fed Spec All Treatment Responses Overall Classification:	Thread Length:	0.438 Inches Minimum And 0.515 Inches Maximum
Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.250 Inches On 797 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Mil-s-6059 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-	Fastener Length:	1.266 Inches Minimum And 1.312 Inches Maximum
Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.250 Inches Grip Length: 0.797 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5026 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd	Head Style:	Hexagon
Hole Diameter: 0.046 Inches Nominal Nominal Thread Diameter: 0.250 Inches Grip Length: 0.797 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Head Onfiguration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Nominal Thread Diameter: 0.250 Inches Grip Length: 0.797 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-6056 Mil Spec 1st Material Response Overall Or Mil-s-6058 Mil Spec 2th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Grip Length: 0.797 Inches Minimum And 0.828 Inches Maximum Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds Per Square Inch Hexagon Flats Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Ocument And Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Hole Diameter:	0.046 Inches Nominal
Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Ocument And Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Nominal Thread Diameter:	0.250 Inches
Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Document And Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Grip Length:	0.797 Inches Minimum And 0.828 Inches Maximum
Features Provided: Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Hole Quantity:	1
Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Hole Type:	Drilled
Minimum Tensile Strength: Hardness Rating: Hole Configuration Style: Material: Material: Material Document And Classification: Surface Treatment: Document And Classification: Material: Cadmium Overall And Chromate Overall Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification: Minimum Tensile Strength: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hexagon Flats Steel Comp 4037 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response O	Features Provided:	Finished Head
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Ocument And Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Thread Quantity Per Inch:	28
Hole Configuration Style: Hexagon Flats Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mi	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Hole Configuration Style:	Hexagon Flats
Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Material:	
Surface Treatment Document And Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn
Document And Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN4H12A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.