

P/N AN4H21A

Military-Fasteners.com

Description

length: 2-5/32", grip: 1-11/16", thread: 1/4-28, cadmium plated steel undrilled shank - drilled head

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN4H21A
Minimum Qty (MOQ):	10
NSN:	5306-00-180-3360
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN4H21A Specifications

read Class: read Direction:	3a Right-hand
	Right-hang
read Length:	0.468 Inches Minimum
stener Length:	2.156 Inches Nominal
ad Style:	Hexagon
ad Height:	0.140 Inches Minimum And 0.172 Inches Maximum
dth Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
le Diameter:	0.046 Inches Nominal
minal Thread Diameter:	0.250 Inches
	1.688 Inches Nominal
p Length:	
le Quantity:	
le Туре:	Drilled
atures Provided:	Finished Head
read Quantity Per Inch:	28
nimum Tensile Strength:	125000 Pounds Per Square Inch
rdness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
le Configuration Style:	Hexagon Flats
terial:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
terial Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
rface Treatment:	Cadmium Overall And Chromate Overall
rface Treatment Document And ssification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
read Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/AN4H21A</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.