

Description

Length: 4", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 15/32", AN4 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN4H40A
Minimum Qty (MOQ):	5
NSN:	5306-00-638-5753
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN4H40A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Minimum
Fastener Length:	4.031 Inches Nominal
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	3.562 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN4H40A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.