

P/N AN5-20

Description

length: 2-3/32", grip: 1-9/16", thread: 5/16-24, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN520

Minimum Qty (MOQ): 25

NSN: 5306-01-382-3781

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N AN5-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.531 Inches Nominal
Fastener Length:	2.093 Inches Nominal
Head Style:	Hexagon
Head Height:	0.122 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN5-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.