

## **P/N AN5-34**

### **Description**

Length: 3-19/32", grip: 3-1/16", thread: 5/16-24, cadmium plated steel drilled shank

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN534
Minimum Qty (MOQ):	10
NSN:	5306-00-151-0909
ECCN:	EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN5-34 Specifications**

Thread Direction: Right-hand Thread Length: 0.532 Inches Minimum Fastener Length: 3.594 Inches Nominal Head Style: Hexagon Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Width Between Flats: 0.706 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 3.062 Inches Nominal First Hole Nominal Thread Diameter: 3.120 Inches Grip Length: 3.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 42 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 5teel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8730 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: 2admium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unif		
Thread Length:  5.532 Inches Minimum  5.544 Inches Nominal  Head Style: Head Style: Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum  Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Nominal Features Provided: Finished Head  Thread Quantity Per Inch: 44 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 0.540 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center:  Material:  Material: Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Thread Class:	3a
Fastener Length:  Head Style:  Hexagon  Head Height:  0.172 Inches Minimum And 0.204 Inches Maximum  Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum  Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole  Nominal Thread Diameter: 0.312 Inches  Grip Length: Features Provided: Finished Head  Thread Quantity Per Inch: 44  Minimum Tensile Strength: 125000 Pounds Per Square Inch  Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  Distance From Head Largest Bearing Surface To Shank Hole Center:  Material:  Material:  Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall  Surface Treatment Document And Classification: Q-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Thread Direction:	Right-hand
Head Style: Hexagon  Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum  Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum  Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole  Nominal Thread Diameter: 0.312 Inches  Grip Length: 3.062 Inches Nominal  Features Provided: Finished Head  Thread Quantity Per Inch: 24  Minimum Tensile Strength: 125000 Pounds Per Square Inch  Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  Distance From Head Largest Bearing Surface To Shank Hole Center: 3.421 Inches Nominal First Hole  Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall  Surface Treatment: 0.4c1, vip 2, class 3 Fed Spec All Treatment Responses Overall  Surface Treatment Document And Classification: 0.7c1, class 3 Fed Spec All Treatment Responses Overall	Thread Length:	0.532 Inches Minimum
Head Height:  0.172 Inches Minimum And 0.204 Inches Maximum  Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum  5 hank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole  Nominal Thread Diameter: 0.312 Inches  Grip Length: 3.062 Inches Nominal  Features Provided: Finished Head  Thread Quantity Per Inch: 44 Minimum Tensile Strength: 125000 Pounds Per Square Inch  Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  Distance From Head Largest Bearing Surface To Shank Hole Center:  Material:  Material:  Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall  Mil-b-6812 Mil Spec All Material Responses Overall  Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Fastener Length:	3.594 Inches Nominal
Width Between Flats:0.490 Inches Minimum And 0.502 Inches MaximumShank Unthreaded Hole Diameter:0.076 Inches Nominal First HoleNominal Thread Diameter:0.312 InchesGrip Length:3.062 Inches NominalFeatures Provided:Finished HeadThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:3.421 Inches Nominal First HoleMaterial:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 OverallMaterial Document And Classification:Mil-b-6812 Mil Spec All Material Responses OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Head Style:	Hexagon
Shank Unthreaded Hole Diameter:  Nominal Thread Diameter:  0.312 Inches Grip Length: 3.062 Inches Nominal Features Provided: Thread Quantity Per Inch: 44 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center:  Material:  Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Nominal Thread Diameter: 0.312 Inches Grip Length: 3.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 3.421 Inches Nominal First Hole Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Grip Length: 3.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 3.421 Inches Nominal First Hole  Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mill-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Features Provided:  Thread Quantity Per Inch:  Minimum Tensile Strength:  125000 Pounds Per Square Inch  12500 Pounds Per Square Inch  125000 Pounds Per Square Inch  12500 Pounds Per Squ	Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:  Minimum Tensile Strength:  125000 Pounds Per Square Inch  Hardness Rating:  26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  Distance From Head Largest Bearing Surface To Shank Hole Center:  Material:  Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall  Material Document And Classification:  Mil-b-6812 Mil Spec All Material Responses Overall  Surface Treatment:  Cadmium Overall And Chromate Overall  Surface Treatment Document And Classification:  Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Grip Length:	3.062 Inches Nominal
Minimum Tensile Strength:  Hardness Rating:  26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  Distance From Head Largest Bearing Surface To Shank Hole Center:  Material:  Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall  Material Document And Classification:  Mil-b-6812 Mil Spec All Material Responses Overall  Surface Treatment:  Cadmium Overall And Chromate Overall  Surface Treatment Document And Classification:  Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Features Provided:	Finished Head
Hardness Rating:  Distance From Head Largest Bearing Surface To Shank Hole Center:  Material:  Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall  Material Document And Classification:  Mil-b-6812 Mil Spec All Material Responses Overall  Surface Treatment:  Cadmium Overall And Chromate Overall  Surface Treatment Document And Classification:  Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:  Material:  Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall  Material Document And Classification:  Mil-b-6812 Mil Spec All Material Responses Overall  Surface Treatment:  Cadmium Overall And Chromate Overall  Surface Treatment Document And Classification:  Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Shank Hole Center:  Material:  Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall  Material Document And Classification:  Mil-b-6812 Mil Spec All Material Responses Overall  Surface Treatment:  Cadmium Overall And Chromate Overall  Surface Treatment Document And Classification:  Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:  Comp 8740 Overall Or Steel Comp 4140 Overall  Material Document And Classification:  Mil-b-6812 Mil Spec All Material Responses Overall  Surface Treatment:  Cadmium Overall And Chromate Overall  Surface Treatment Document And Classification:  Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall		3.421 Inches Nominal First Hole
Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Material:	
Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
CAT STATE OF THE S	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/AN5-34">https://military-fasteners.com/bolts/machine+bolts/AN5-34</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.