

P/N AN5-47

Description

length: 4-31/32", grip: 4-7/16", thread: 5/16-24, cadmium plated steel, drilled shank

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: AN547

Minimum Qty (MOQ):

NSN: 5306-00-150-9391

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN5-47 Specifications

Thread Direction: Right-hand 15		
Tread Length: 0.531 Inches Minimum Fastener Length: 4.969 Inches Nominal Head Style: Hexagon Width Between Flats: 0.490 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Onominal Thread Diameter: 0.312 Inches Grip Length: 4.438 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 4.797 Inches Nominal First Hole Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Material Document And Classification: 5.77 Mil Spec 6th Material Response Overall Or Mil-s-6098 Mil Spec 2th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material R	Thread Class:	3a
Head Style: Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Width Between Flats: 0.076 Inches Nominal First Hole Shank Unthreaded Hole Diameter: 0.312 Inches Grip Length: 4.438 Inches Nominal First Hole Nominal Thread Diameter: 4.438 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 25000 Pounds Per Square Inch Hardness Rating: 4.797 Inches Nominal First Hole Distance From Head Largest Bearing Surface To Shank Hole Center: Ary Inches Nominal First Hole Material: 5teel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Material Document And Classification: 5teel Comp 4140 Overall Or Mils-s-6050 Mil Spec 4th Material Response Overall Or Mils-s-6098 Mil Spec 5th Material Response Overall Or Mils-s-6098 Mils Spec 5th Materia	Thread Direction:	Right-hand
Head Style: Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Nominal Thread Diameter: 0.312 Inches Onominal Thread Diameter: 0.312 Inches Nominal Thread Diameter: 0.312 Inches Features Provided: 4.438 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 35 Eteel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Material Document And Classification: 45 Mil-s-6056 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spe	Thread Length:	0.531 Inches Minimum
Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 4.438 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 4140 Overall Or Steel Comp 8735 Overall Material: Steel Comp 4140 Overall Or Steel Comp 8735 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec Sth Material Response Overall Or Mil-s-6098 Mil Spec Sth Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Ove	Fastener Length:	4.969 Inches Nominal
Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum 0.076 Inches Nominal First Hole 0.312 Inches Nominal Thread Diameter: 0.312 Inches Grip Length: 4.438 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 05.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Mil-s-2656 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Respo	Head Style:	Hexagon
Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 4.438 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 4.797 Inches Nominal First Hole Material: 5teel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8755 Overall Material Document And Classification: 6Teatment: 6Addium Overall And Chromate Overall Or Ams 6300 Assn Std 6th Material Response Overall Graph Glassification: 6Teatment Document And Classification: 6Teatment Patent Pate	Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Nominal Thread Diameter: Grip Length: 4.438 Inches Nominal Features Provided: Finished Head Finished Head Thread Quantity Per Inch: 44 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material: Material Document And Classification: Mill-s-2656 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec Sth Material Response Overall Or Mil-s-6098 Mil	Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
A438 Inches Nominal	Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Finished Head Thread Quantity Per Inch: Minimum Tensile Strength: 125000 Pounds Per Square Inch 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Mil-s-2656 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-60757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Oq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall Oq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch: Minimum Tensile Strength: 125000 Pounds Per Square Inch 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall 4.797 Inches Nominal First Hole 3500 Pounds Per Square Inch 4.797 Inches Nominal First Hole 4.797 Inches Nominal First Hole 4.797 Inches Nominal First Hole 5500 Pounds Per Square Inch 5500 Pounds Per Square Inch 4.797 Inches Nominal First Hole 5500 Pounds Per Square Inch 5500	Grip Length:	4.438 Inches Nominal
Minimum Tensile Strength: Hardness Rating: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material Document And Classification: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Steel Comp Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6000 Assn Std 6th Material Response Overal	Features Provided:	Finished Head
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall 4.797 Inches Nominal First Hole 4.797 Inches Nominal First Hole Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Material Document And Classification: Mil-s-2656 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	24
A.797 Inches Nominal First Hole Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Material Document And Classification: Mil-s-2656 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
4.797 Inches Nominal First Hole Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: 4.797 Inches Nominal First Hole Steel Comp 8740 Overall Or Steel Comp 1022 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Qq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material: Material Document And Classification: Overall Or Steel Comp 8735 Overall Mil-s-2656 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Oq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall Overall Or Steel Comp 8735 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Oq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall	Distance From Head Largest Bearing Surface To Shank Hole Center:	4.797 Inches Nominal First Hole
Response Overall Or Mil-s-6050 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6757 Mil Spec 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Classification: Qq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall	Material:	
Surface Treatment Document And Classification: Qq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	Response Overall Or Mil-s-6050 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-
Qq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall Classification:	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,ty2,cl3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN5-47 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/AN5-47 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/AN5-47 and selecting the quantity you want then click "add to cart".