

P/N AN5-50A

Military-Fasteners.com

Description

length: 5-3/32", grip: 4-9/16", thread: 5/16-24, cadmium plated steel undrilled shank"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN550A
Minimum Qty (MOQ):	2
NSN:	5306-00-151-1153
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN5-50A Specifications

hread Class: 3a	
hread Direction: Right-han	d
hread Length: 0.500 Incl	hes Minimum And 0.578 Inches Maximum
astener Length: 5.078 Incl	hes Minimum And 5.125 Inches Maximum
lead Style: Hexagon	
lead Height: 0.172 Incl	hes Minimum And 0.204 Inches Maximum
Vidth Between Flats: 0.490 Incl	hes Minimum And 0.502 Inches Maximum
ominal Thread Diameter: 0.312 Incl	hes
rip Length: 4.547 Incl	hes Minimum And 4.578 Inches Maximum
eatures Provided: Finished H	fead
hread Quantity Per Inch: 24	
linimum Tensile Strength: 125000 P	ounds Per Square Inch
ardness Rating: 26.0 Rock	well C Minimum Overall And 32.0 Rockwell C Maximum Overall
laterial:	np 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or np 4037 Overall
laterial Document And lassification:	6 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material e Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn laterial Response Overall
urface Treatment: Cadmium	Overall And Chromate Overall
urface Treatment pocument And Qq-p-416 lassification:	type 2,class 3 Fed Spec All Treatment Responses Overall,
hread Series Designator: Unf	

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/AN5-50A</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.