



★ FASTENERS

Military-Fasteners.com

P/N AN5-63A

Description


length: 6-15/32", grip: 5-15/16", thread: 5/16-24, cadmium plated steel undrilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN563A
Minimum Qty (MOQ):	2
NSN:	5306-01-323-8963
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN5-63A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.531 Inches Nominal
Fastener Length:	6.453 Inches Minimum And 6.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.309 Inches Minimum And 0.312 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN5-63A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.