

**Description**

Fastener Length: 6-19/32", Thread: 1/4-24, Thread Length: 17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN564
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-151-1309
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN5-64 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.532 Inches Minimum
<b>Fastener Length:</b>	6.594 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.172 Inches Minimum And 0.204 Inches Maximum
<b>Width Between Flats:</b>	0.490 Inches Minimum And 0.502 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	6.062 Inches Nominal
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	6.421 Inches Nominal First Hole
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Mil-b-6812 Mil Spec All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN5-64> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.