

Description

Fastener Length: 1-3/4", Hole Diameter: 3/64", Thread: 10-24, Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | AN500A1028 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-180-0035 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N AN500A10-28 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.688 Inches Minimum And 1.750 Inches Maximum |
| Fastener Length: | 1.688 Inches Minimum And 1.750 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.292 Inches Minimum And 0.313 Inches Maximum |
| Head Height: | 0.123 Inches Minimum And 0.130 Inches Maximum |
| Hole Diameter: | 0.047 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-633 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Head Hole Configuration Style: | Round Longitudinal Hole |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 1 Type And 5s Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500A10-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.