



Military-Fasteners.com

P/N AN500A10-6

Description

Fastener Length: 3/8", Hole Diameter: 3/64", Thread: 10-24, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN500A106
Minimum Qty (MOQ):	25
NSN:	5305-00-151-0353
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN500A10-6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Minimum
Fastener Length:	0.375 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.123 Inches Minimum And 0.130 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 5s Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500A10-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.