

P/N AN500A2-10

Description

Fastener Length: 5/8", Hole Diameter: ", Thread: 2-56, Thread Length: 5/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN500A210

Minimum Qty (MOQ): 25

NSN: 5305-00-206-6907

Schedule B: 7318.15.2010

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N AN500A2-10 Specifications

Thread Class: Thread Direction: Right-hand Thread Length: 0.589 Inches Minimum And 0.625 Inches Maximum	
Throad Longth: 0.580 Inches Minimum And 0.625 Inches Maximum	
o.569 files Millimum And 0.025 files Maximum	
Fastener Length: 0.625 Inches Nominal	
Head Style: Fillister	
Head Diameter: 0.124 Inches Minimum And 0.140 Inches Maximum	
Head Height: 0.055 Inches Minimum And 0.062 Inches Maximum	
Hole Diameter: 0.031 Inches Nominal	
Internal Drive Style: Cross Recess Type 1	
Nominal Thread Diameter: 0.086 Inches	
Hole Quantity: 1	
Thread Quantity Per Inch: 56	
Minimum Tensile Strength: 60000 Pounds Per Square Inch	
Screw Material: Steel Or Steel Comp 1010	
Screw Material Document And Classification: Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec Material Response	2nd
Screw Surface Treatment: Cadmium	
Screw Surface Treatment Document And Classification: Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response	
Head Hole Configuration Style: Round Longitudinal Hole	
Thread Series Designator: Unc	

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN500A2-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.