



Military-Fasteners.com

P/N AN500A3-10

Description

Fastener Length: 5/8", Hole Diameter: 1/32", Thread: 3-48, Thread Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN500A310
Minimum Qty (MOQ):	40
NSN:	5305-00-207-0173
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN500A3-10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.583 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.145 Inches Minimum And 0.161 Inches Maximum
Head Height:	0.064 Inches Minimum And 0.070 Inches Maximum
Hole Diameter:	0.037 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.099 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	48
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500A3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.