

P/N AN500A4-7

Description

Fastener Length: 7/16", Thread: 4-40, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN500A47

Minimum Qty (MOQ): 500 EA

NSN: 5305-00-206-2607

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN500A4-7 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.388 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.438 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.166 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.072 Inches Minimum And 0.079 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN500A4-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.