

Description

Fastener Length: 1-3/4", Hole Diameter: 3/64", Thread: 1/4-20, Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN500A41628
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-144-3907
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN500A416-28 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	1.750 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.389 Inches Minimum And 0.414 Inches Maximum
Head Height:	0.161 Inches Minimum And 0.170 Inches Maximum
Hole Diameter:	0.050 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500A416-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.