

Description

Fastener Length: 7/8", Hole Diameter: 1/32", Thread: 6-32, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | AN500A614 |
| Minimum Qty (MOQ): | 60 EA |
| NSN: | 5305-00-151-0384 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |



P/N AN500A6-14 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.813 Inches Minimum And 0.875 Inches Maximum |
| Fastener Length: | 0.875 Inches Nominal |
| Head Style: | Fillister |
| Head Diameter: | 0.208 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.089 Inches Minimum And 0.096 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Screw Material: | Steel Or Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Head Hole Configuration Style: | Round Longitudinal Hole |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500A6-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.