

Description

Fastener Length: 1-1/8", Hole Diameter: 1/32", Thread: 6-32, Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN500A618
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-151-0382
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN500A6-18 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.063 Inches Minimum And 1.125 Inches Maximum
Fastener Length:	1.125 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.096 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Astm A575 Assn Std 2nd Material Response Or Astm A576 Assn Std 3rd Material Response Or Astm A108 Assn Std 4th Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty1 Cl3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500A6-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.