

P/N AN500A6-28

Military-Fasteners.com

Description

Fastener Length: 1-3/4", Hole Diameter: 1/32", Thread: 6-32, Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	AN500A628
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-151-0379
Schedule B:	7318.15.6080
ECCN:	9A991



P/N AN500A6-28 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Fastener Length:	1.750 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.096 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/AN500A6-28</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.