

# P/N AN500A6-8

## **Description**

Fastener Length: 1/2", Hole Diameter: 3/64", Thread: 6-32, Thread Length: 7/16", drilled head

\* Manufacturer certifications are shipped with your order EREE of charge

# Order this part online

#### **Additional Information**

SKU / Model: AN500A68

Minimum Qty (MOQ): 50

NSN: 5305-00-151-0387

Schedule B: 7318.15.6080

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N AN500A6-8 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.096 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

### **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN500A6-8">https://military-fasteners.com/screws/machine+screws/AN500A6-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/AN500A6-8">https://military-fasteners.com/screws/machine+screws/AN500A6-8</a> and selecting the quantity you