

**Description**

Fastener Length: 3/4", Hole Diameter: 3/64", Thread: 8-32, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN500A812                                 |
| Minimum Qty (MOQ):      | 20 EA                                     |
| NSN:                    | 5305-00-151-0369                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN500A8-12 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 2a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.719 Inches Minimum And 0.750 Inches Maximum         |
| <b>Fastener Length:</b>                                     | 0.719 Inches Minimum And 0.750 Inches Maximum         |
| <b>Head Style:</b>  | Fillister   |
| <b>Head Diameter:</b>                                       | 0.250 Inches Minimum And 0.270 Inches Maximum         |
| <b>Head Height:</b>   | 0.106 Inches Minimum And 0.113 Inches Maximum         |
| <b>Hole Diameter:</b>                                       | 0.047 Inches Nominal                                  |
| <b>Internal Drive Style:</b>                                | Slot  |
| <b>Nominal Thread Diameter:</b>                             | 0.164 Inches  |
| <b>Hole Quantity:</b>                                       | 1   |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 60000 Pounds Per Square Inch                          |
| <b>Screw Material:</b>                                      | Steel Comp 1010                                       |
| <b>Screw Material Document And Classification:</b>          | Qq-s-633 Fed Spec Single Material Response            |
| <b>Screw Surface Treatment:</b>                             | Cadmium   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| <b>Head Hole Configuration Style:</b>                       | Round   |
| <b>Thread Series Designator:</b>                            | Unc   |
| <b>Nondefinitive Spec/std Data:</b>                         | 1 Type And 5s Style                                   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500A8-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.